





RoHS

NOTES:

1. Material: PA66, UL94V-0
2. Color: White
3. Current Rating: 1A AC,DC
4. Voltage Rating: 50V AC,DC
5. Temperature Rang: -25°C~+85°C
6. Contact Resistance: 30mΩ Max
7. Insulation Resistance: 100MΩ Min
8. Withstanding Voltage: 500V AC/minute
9. Ordering Code: A1005HA-2xNP-XX

Color



| PIN  | DIM. (mm) |       |       |
|------|-----------|-------|-------|
|      | A         | B     | C     |
| 2X10 | 9.00      | 14.70 | 15.70 |
| 2X15 | 14.00     | 19.70 | 20.70 |
| 2X20 | 19.00     | 24.70 | 25.70 |
| 2X25 | 24.00     | 29.70 | 30.70 |

| DATE | REV | ECN NO | DESCRIPTION | MODIFY | APPROVAL |
|------|-----|--------|-------------|--------|----------|
| 1    |     | 2      |             | 4      |          |

| GENERAL TOLERANCE |       |
|-------------------|-------|
| .X                | ±0.30 |
| .XX               | ±0.20 |
| .XXX              | ±0.10 |
| X.*               | ±2°   |
| PROJECT           |       |
|                   |       |








东莞市国亚电子有限公司  
Dong Guan Guo Ya Connectors co., Ltd.

| APPROVAL     | CHECK       | DRAWN       | DATE       |
|--------------|-------------|-------------|------------|
| Yangzhengguo | Yangzhengyi | Lvtiansheng | 2016/08/26 |

| PARTNO.                        |       |       |     |        |
|--------------------------------|-------|-------|-----|--------|
| A1005HA-2*NP-XX                |       |       |     |        |
| TITLE                          |       |       |     |        |
| 1.00 mm Crimp Style Connectors |       |       |     |        |
| UNIT                           | SCALE | SHEET | REV | NUMBER |
| mm                             | 1:1   | 1/1   | A0  | A-040  |

RoHS



NOTES:

1. Material: Phosphor Bronze, T=0.12mm
2. Finish: TPE-Tin Plated Over Nickel.  
GPE-Gold Flash Over Nickel.  
G1PE-Gold 1u" Over Nickel.  
G3PE-Gold 3u" Over Nickel.  
G5PE-Gold 5u" Over Nickel.  
G15PE-Gold 15u" Over Nickel.
3. Applicable Wire Range: AWG#28~#32
4. Insulation O.D.: 0.80mm (Max.)
5. Current Rating: 1A AC,DC
6. Voltage Rating: 50V AC,DC
7. Temperature Rang: -25°C~+85°C
8. Contact Resistance: 30mΩ Max
9. Insulation Resistance: 100MΩ Min
10. Withstanding Voltage: 500V AC/minute
11. Ordering Code: A1005T-xxx

Finish See Note 2



GENERAL TOLERANCE

.X ±0.30

.XX ±0.20

.XXX ±0.10

X.\* ±2°

PROJECT



东莞市国亚电子有限公司  
Dong Guan Guo Ya Connectors co., Ltd.

APPROVAL

Yangzhengguo

CHECK

Yangzhengyi

DRAWN

Lvtiansheng

DATE

2016/08/26

PARTNO.

A1005T-XXX

TITLE

1.00 mm Crimp Style Connectors

UNIT

mm

SCALE

1:1

SHEET

1/1

REV

A0

NUMBER

A-041

DATE

1

REV

2

DESCRIPTION

3

MODIFY

4

APPROVAL

5

APPROVAL

6

CHECK

7

DRAWN

8

DATE

9

UNIT

10

SCALE

11

SHEET

12

REV

13

NUMBER

14